# Technical data sheet Wireless accessories

ConnectClip is an intermediate device, which wirelessly connects Oticon 2.4GHz wireless hearing aids through Bluetooth to most mobile phones.

ConnectClip further doubles as a remote/partner microphone for improved 1-to-1 speech understanding in adverse listening situations.

### **Headset for mobile phones**

ConnectClip can be paired with most mobile phones through Bluetooth, in effect turning the hearing instruments into a high-quality headset. Sound from the mobile phone is streamed wirelessly directly to the hearing aids, while the ConnectClip's directional microphones pick up the wearer's voice.

# Headphones for music (A2DP)

Audio/music from a Bluetooth-connected mobile phone, MP3 player etc. is streamed directly in stereo to both hearing aids.

#### Remote/Partner microphone

The ConnectClip works in a special mode as a remote/partner microphone for improved intelligibility of the speaker wearing it, either at a distance (up to 20 metres), in a very noisy environment, or in a combination of the two.

## PC/Laptop/Computer

It can at times be difficult to pair/connect directly to a computer's built-in Bluetooth. To overcome any issues, ConnectClip can be used with the BTD800 USB dongle for easy/hassle-free connectivity.

For more information please visit: www.oticon.ca

# ConnectClip



The ConnectClip is a multipurpose device which empowers today's Oticon hearing aid users to participate and interact in a number of everyday situations which are at best difficult and at worst impossible, even with the best hearing instruments.





- Regular and long lanyard
- Power adapter for charging
- USB charge cable
- Protective pouch
- Protective skin







USB	cha	rain
030	CHa	ı yıı ı

Technical data		
Name/model	ConnectClip/AC1A	
FCC/IC	FCC ID: 2ACAHACO1 IC: 11936A-ACO1	
Compatibility	Oticon 2.4GHz wireless hearing instruments	
Dimensions	53 x 27 x 18 mm; weight 27 g	
Conditions of use	Transportation and storage conditions: Temperature and humidity shall not exceed the below limits for extended periods during transportation and storage: • Temperature: -20°C to +60°C • Humidity: 15 - 93%, noncondensing  Operational environment conditions: • Temperature: +5°C to 40°C • Humidity: 15 - 93%, noncondensing	
	Atmospheric pressure: 700 hPa to 1060 hPa	
System features	Mobile phone headset (handsfree/headset profile) & Stereo Music (A2DP) Remote/Partner Microphone	
Remote control of HI	Volume, program shift and mute of microphones in hearing instruments	
Battery <sup>1</sup>	Typical daily use 16 hours: 2 hours audio streaming + 2 hours phone + 12 hours standby. 36 h stand by (turned on, no streaming) Charge time 2 hours Battery total life expectancy: 80% capacity left after 720 charge/re-charge cycles	
Audio quality <sup>2</sup>	Stereo/20 kHz sample freq.	
Audio bandwidth <sup>2</sup>	80 Hz - 10 kHz	
Pairing details	Up to 8 paired Bluetooth devices	
Bluetooth compliance	Version 4.2 + EDR	
Bluetooth profile support	Advanced Audio Distribution Profile (A2DP) 1.3 Headset Profile (HSP) 1.2 Hands-Free Profile (HFP) 1.6 including support for Wideband Speech	
Wireless range <sup>3</sup>	10 metres with Bluetooth Class 2 devices (e.g. mobile phones) up to 20 metres between ConnectClip and hearing instruments	
Streaming frequency	2.4GHz (Bluetooth band)	
Emissions	Max. 17 dBm e.i.r.p. in compliance with all relevant standards	
Status indications	LEDs on the ConnectClip. Acoustic signals in hearing instruments	
Genie 2017.2 (or later)	Firmware upgrade. Fitting of streaming programs	

- 1. Using the supplied charger
- 2. Actual audio performance depending on client's hearing instruments
- 3. Free line of sight between the ConnectClip and other devices. Other devices operating in the 2.4GHZ band may interfere and reduce range.



Manufactured par : SBO Hearing A/S Kongebakken 9 DK-2765 Smørum Danemark www.sbohearing.com Imported and Distributed by : Audmet Canada Ltd 1600-4950 Yonge St Toronto, ON M2N 6K1 www.oticon.ca



Waste from electronic equipment must be handled according to local regulations.



